Figure: 25 TAC §289.301(cc)(1)

Wavelength (nm)	Emission duration (seconds)	Class I - Accessible Emission limits		
		(value)	(units)	(quantity)
≥180 but ≤400	≤3.0×10^{4}	$2.4\times10^{-5}k_1k_2$*	Joules (J)*	radiant energy
	>3.0×10^{4}	$8.0\times10^{-10}k_1k_2$*	Watts (W)*	radiant power
>400 but ≤1400	>1.0×10^{-9} to 2.0×10^{-5}	$2.0\times10^{-7}k_1k_2$	J	radiant energy
	>2.0×10^{-5} to 1.0×10^{1}	$7.0\times10^{-4}k_1k_2\ t^{3/4}$	J	radiant energy
	>1.0×10^{1} to 1.0×10^{4}	$3.9\times10^{-3}k_1k_2$	J	radiant energy
	>1.0×10^{4}	$3.9\times10^{-7}k_1k_2$	W	radiant power
	OR			
	>1.0×10^{-9} to 1.0×10^{1}	$10k_1k_2t^{a}$	J $cm^{-2}sr^{-1}$	integrated radiance
	>1.0×10^{1} to 1.0×10^{4}	$20k_1k_2$	J $cm^{-2}sr^{-1}$	integrated radiance
	>1.0×10^{4}	$2.0\times10^{-3}k_1k_2$	W $cm^{-2}sr^{-1}$	radiance
>1400 but ≤2500	>1.0×10^{-9} to 1.0×10^{-7}	$7.9\times10^{-5}k_1k_2$	J	radiant energy
	>1.0×10^{-7} to 1.0×10^{1}	$4.4\times10^{-3}k_1k_2t^{¼}$	J	radiant energy
	>1.0×10^{1}	$7.9\times10^{-4}k_1k_2$	W	radiant power
>2500 but ≤1.0×10^{6}	>1.0×10^{-9} to 1.0×10^{-7}	$1.0\times10^{-2}k_1k_2$	J cm^{-2}	radiant exposure
	>1.0×10^{-7} to 1.0×10^{1}	$5.6\times10^{-1}k_1k_2t¼$	J cm^{-2}	radiant exposure
	>1.0×10^{1}	$1.0\times10^{-1}k_1k_2t$	J cm^{-2}	radiant exposure

The variable in the expression is the magnitude of the sampling interval (t), in units of seconds

* Class I accessible emission limits for wavelengths equal to or greater than 180 nm but less than or equal to 400 nm shall not exceed the class I accessible emission limits for the wavelengths greater than 1400 nm but less than or equal to 1.0×10^{6} nm with a k_1 and k_2 of 1.0 for comparable sampling intervals.